

DURALITE
Series 500
Single-Tilt Aluminum Window





Discover the Duralite difference.

DURALITE

Series 500

Single-Tilt Aluminum Window



Features:

- 2 1/2" Thick heavy duty main frame.
- .062" thickness and 6063-T5 aluminum alloy on all main and sash frames.
- Thermally broken main and sash frames to reduce cool and heat transfer.
- Double weatherstrip on sash with wool pile and fin seal.
- 3/4" insulated glass using Tremco "Swiggle Strip."
- 5/8" heavy duty spiral sash balances.
- Lower sash operates and tilts in for easy cleaning.
- Installation fins and anchors are .050" thickness and 6063-T5 alloy.

Options:

- Colors . . . : Bronze or white, baked on enamel finish.
- Glass : Clear or gray tinted glass in stock. (Specialty glass also available upon request)
- Lites : Multi-lites available upon request.
- Screen : Standard fiberglass wire or "Sunscreen."
- Flanges . . . : Replacement (No flanges).
Mobile home flange (flange on outer edge).
Prime window flange (flange in center).
- Windows can be mullied together to accommodate larger openings.

Replaces wood or aluminum windows, also some jalouses and casements.

Our performance pledge:

**Every Duralite product is backed by our pledge of quality performance in material, workmanship and service after the sale.
Your satisfaction is our only measure of success.**